Appendix D

Calibration Certificate for Construction Noise Monitoring Equipment





20±2 °C

<80% R.H.

Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Page 1 of 1

Report no.: 212769CA212069(2)

CALIBRATION CERTIFICATE OF SOUND LEVEL METER

Client Supplied Information

Client : Fugro Technical Services Ltd.

Address : Room 723 & 725, 7/F., Block B Profit Industrial Building, 1-15 Kwai Fung Crescent, Kwai Chung, N.T. Project : Calibration Services

Details of Unit Under Test, UUT

Description	:	Sound Level Meter		
Manufacturer	÷	Casella		
		Meter	Microphone	Preamplifier
Model No.	;	CEL-63X	CE-251	CEL-495
Serial No.	:	1488295	01163	004064
Equipment ID	:	N-54		
Next Calibration Date	:	25-Aug-2022		
Specification Limit	:	EN 61672-1: 2003 Class	1	

Laboratory Information

Details of Reference Equipment -

Description	1	B & K Acoustic Multifunction Calibrator 4226 (Traditional free field setting)
Equipment ID.	:	R-108-1

Date of Calibration	:	26-Aug-2021		
Calibration Location	÷	Calibration Laboratory of FTS	Ambient Temperature	:
Method Used	;	By direct comparison	Relative Humidity	:

Calibration Results :

Parameters		Mean Value (dB)	Specific	ation	Limit(dB)
	4000Hz	2.3	2.6	to	-0.6
A-weigthing frequency response	2000Hz	1.5	2.8	to	-0.4
	1000Hz	0.0	1.1	to	-1.1
	500Hz	-3.4	-1.8	to	-4.6
	250Hz	-8.8	-7.2	to	-10.0
	125Hz	-16.3	-14.6	to	-17.6
	63Hz	-26.3	-24.7	to	-27.7
	31.5Hz	-39.0	-37.4	to	-41.4
Differential level	94dB-104dB	0.1		± 0.6	3
linearity	104dB-114dB	0.1		± 0.6	6

Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. The expanded uncertainty is 0.3 dB with a coverage factor of 2 at a confidence level of 95%.
- 4. For calibration: Reference SPL are 94, 104 & 114dB, range setting is 20-140dB & time weighting is fast
- 5. The UUT does comply with EN 61672-1: 2003 Class 1 sound level meter for the above measurement.
- 6. The values given in this Calibration Certificate only relate to unit under test and the values measured at the time of the test. Any uncertainties will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during tranportation, overloading, mis-handling or the capability of any other laboratory to repeat the measurement.

Checked by :	🗸 Date : _	27-8-2021 Certified by : KI Joung Date : 1-8-2021
CA-R-297 (22/07/2009)		Leung Kwok Tai (Assistant Manager)
		** End of Report **

The copyright of this report is owned by Fugro Technical Services Limited. This report shall not be reproduced except in full.



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Report no.: 212769CA221660

Page 1 of 1

CALIBRATION CERTIFICATE OF SOUND LEVEL METER

Client Supplied Information

Client : Fugro Technical Services Ltd. Project : Calibration Services

Details of Unit Under Test, UUT

Description		Sound Level Meter		
Manufacturer	:	Casella		
		Meter	Microphone	Preamplifier
Model No.	;	CEL-63X	CE-251	CEL-495
Serial No.	:	0873599	02374	003916
Equipment ID	:	N/A		
Next Calibration Date	:	13-Jul-2023		
Specification Limit	:	EN 61672-1: 2003 Class	s 1	

Laboratory Information

Details of Reference Equipment -

Botallo of Molefelloc	-	quipinon			
Description :		B & K Acoustic Multifunction Calib	rator 4226 (Traditional f	ree	field setting)
Equipment ID. :		R-108-1			
Date Receipt of UUT		13-Jul-2022			
Date of Calibration	;	14-Jul-2022			
Calibration Location	;	Calibration Laboratory of FTS	Ambient Temperature	:	20±2 °C
Method Used		By direct comparison	Relative Humidity		<80% R.H.
As Received	ŝ	Functional / Within specs		÷	
As Returned		Complies with the specification lin	nits (EN61672-1:2003 C	lass	s 1)
Calibration Boculto			,		· · /

Calibration Results :

Parameters		Mean Value (dB)	Specification Limit(dE		Limit(dB)
	4000Hz	1.6	2.6	to	-0.6
A-weigthing frequency response	2000Hz	1.3	2.8	to	-0.4
	1000Hz	0.0	1.1	to	-1.1
	500Hz	-3.3	-1.8	to	-4.6
	250Hz	-8.8	-7.2	to	-10.0
	125Hz	-16.2	-14.6	to	- 17.6
	63Hz	-26.2	-24.7	to	-27.7
Differential level	94dB-104dB	0.0		± 0.6	;
linearity	104dB-114dB	0.0		± 0.6	;

Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. For calibration: Reference SPL are 94, 104 & 114dB, range setting is 20-140dB & time weighting is fast
- 3. The mean value is the average of four measurements.
- 4. A general inspection of the item has been carried out and found the item is in good working conditions.
- 5. The result reported on this certificate apply only to the unit under test as received. Fugro has not been responsible for the sampling stage

Checked by : <u>SUA</u>	Date :	14-7-2022 Certified by: <u>FJ. Jourg</u> Date: <u>15.7-2022</u>
CA-R-297 (22/07/2009)		Leung Kwok Tai (Assistant Manager)
		** End of Report **



Fugro Development Centre 5 Lok Yi Street, Tai Lam Tuen Mun, NT Hong Kong

Report no.: 212769CA212279(2)

Page 1 of 1

CALIBRATION CERTIFICATE OF SOUND CALIBRATOR

Client : Fugro Technical Services Ltd.

Project : Calibration Services

Client Supplied Information

Details of Unit Under Test, UUT

Description		: Sound Calibrator
Manufacturer		: Casella (Model CEL-120/1)
Serial No.		: 5230736
Equipment ID		: N/A
Next Calibration Date	;	12-Sep-2022
Specification Limit		EN 60942: 2003 Class 1

Laboratory Information

Details of Calibration Equipment

Description :	Reference Sound level meter	
Equipment ID. :	R-119-2	
Date of Calibration :	13-Sep-2021	
Calibration Location :	Calibration Laboratory of FTS	Ambient Temperature : 20±2 °C
Method Used :	By direct comparison	Relative Humidity : <80% R.H.

Calibration Results :

Parameters (Setting of UUT) Mean Value (error of measurement)	Specification Limit(dB)
94dB	-0.1 dB	±0.4dB
114dB	-0.1 dB	±0.40B

Remarks:

- 1. The equipment used in this calibration is traceable to recognized National Standards.
- 2. The mean value is the average of four measurements.
- 3. The unit under test complies with the specification limit.
- 4. The values given in this Calibration Certificate only relate to the unit-under-test and the values measured at the time of the test. Any uncertainties quoted will not include allowances for the environmental changes, variation and shock during transportation, or the capability of any other laboratory to repeat the measurement.

Checked by :	_Date : <u>17-9-2021</u>	Certified by: <u>C.T. Journe</u> Date: <u>17-9-707</u>
CA-R-297 (22/07/2009)		Leung Kwok Tai (Assistant Manager)
	**	End of Report **

End of Report